

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	Home Armor Flexible Sealer	
<b>Company Name:</b>	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	<b>Phone Number:</b> (901)775-0100
<b>Web site address:</b>	www.wmbarr.com	
<b>Emergency Contact Information:</b>	3E 24 Hour Emergency Contact W.M. Barr Customer Service	(800)451-8346 (800)398-3892
<b>Product Category:</b>	Waterproofing Sealers	
<b>Synonyms:</b>	BEHFS01, BEHS01HD, EHFS01, EHS01HD, EHFS012CC, EHFS015, EHFS0152C	
<b>Additional Information</b>	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

## 2. HAZARDS IDENTIFICATION

**Flammable Aerosols, Category 1**  
**Gas Under Pressure, Liquefied gas**  
**Skin Corrosion/Irritation, Category 2**  
**Serious Eye Damage/Eye Irritation, Category 1**  
**Toxic To Reproduction, Category 2**  
**Specific Target Organ Toxicity (single exposure), Category 3**  
**Specific Target Organ Toxicity (repeated exposure), Category 2**  
**Simple Asphyxiant**



<b>GHS Signal Word:</b>	<b>Danger</b>
<b>GHS Hazard Phrases:</b>	H222: Flammable aerosol. H280: Containers gas under pressure; may explode if heated. H315: Causes skin irritation. H318: Causes serious eye damage. H335: May cause respiratory irritation. H361: Suspected of damaging fertility or the unborn child. H373: May cause damage to organs through prolonged or repeated exposure.
<b>GHS Precaution Phrases:</b>	P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P211: Do not spray on an open flame or any other ignition source. P251: Pressurized container: Do not pierce or burn, even after use. P260: Do not breathe gas/mist/vapors/spray. P264: Wash hands thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection. P281: Use personal protective equipment as required.
<b>GHS Response Phrases:</b>	P302+352: IF ON SKIN: Wash with plenty of soap and water. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

# SAFETY DATA SHEET

## Home Armor Flexible Sealer

comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical attention/advice.

P310: Immediately call a POISON CENTER or doctor/physician.

P314: Get medical attention/advice if you feel unwell.

P321: Specific treatment see label.

P332+313: If skin irritation occurs, get medical advice/attention.

P362: Take off contaminated clothing and wash before re-use.

### GHS Storage and Disposal Phrases:

P403+233: Store container tightly closed in well-ventilated place.

P405: Store locked up.


P410+403: Protect from sunlight and store in well-ventilated place.

P412: Do not expose to temperatures exceeding 50 °C/122 °F.

P501: Dispose of contents/container according to local, state and federal regulations.

### Hazard Rating System:

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL		0
PPE		X



### HMIS:

### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

### Potential Health Effects (Acute and Chronic):

#### EYES:

Can cause eye irritation with tearing, redness, swelling, or a stinging or burning feeling. Swelling of the eyes with blurred vision is possible. Effects may be more serious with repeated or prolonged contact.

#### SKIN:

May cause mild skin irritation with redness and/or an itching or burning feeling. Can cause scaling or occasionally blistering. Effects may become more serious with repeated or prolonged contact. May absorb through the skin and cause effects similar to those as from inhalation or ingestion.

Although rare, skin contact with propylene glycol may cause allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects).

#### INHALATION:

Breathing high concentrations may be harmful. Mist or vapor can irritate the throat and lungs. Breathing this material may cause central nervous system depression with symptoms including nausea, headache, dizziness, fatigue, drowsiness, or unconsciousness. Breathing high concentrations of this material, for example, in an enclosed space or by intentional abuse, can cause irregular heartbeats which can cause death.

#### INGESTION:

Swallowing this material may be harmful. Swallowing this material may cause stomach or intestinal upset with pain, nausea, and/or diarrhea. This material can get into the lungs during swallowing or vomiting. Small amounts in the lungs can cause lung damage, possibly leading to chronic lung dysfunction or death. Swallowing this material may cause effects similar to those described for inhalation exposure, such as central nervous system depression and effects.

#### CHRONIC OVEREXPOSURE EFFECTS:

Reports have associated repeated and prolonged overexposure to solvents with

# SAFETY DATA SHEET

## Home Armor Flexible Sealer

Page: 3

Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 01/29/2014

neurological and other physiological damage. Intentional misuse by deliberately concentrating and inhaling solvents may be harmful or fatal.

Toluene may cause harm to the fetus based on tests with laboratory animals. Prolonged or repeated overexposure to toluene, has been associated with reproductive effects in experimental animals and in long-term chemical abuse situations. Long-term overexposure to toluene has been associated with impaired color vision and hearing damage.

Chronic overexposure to components of this material may cause systemic toxicity, including adverse reactions to the following: kidney, liver, spleen, adrenals, lungs, skin, blood, testes, cardiovascular and nervous systems.

#### TARGET ORGANS:

Kidneys, lungs, liver, mucous membranes, heart, upper respiratory tract, skin, auditory system, central nervous system, eye, digestive system

PRIMARY ROUTES OF ENTRY: inhalation, skin, ingestion

**Medical Conditions Generally Aggravated By Exposure:** Disorders of the: skin, respiratory system, liver, kidneys, central nervous system, heart, auditory system

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
108-88-3	Toluene {Benzene, Methyl-; Toluol}	10.0 -30.0 %	XS5250000
64742-95-6	Petroleum Hydrocarbons	10.0 -30.0 %	WF3400000
1317-65-3	Limestone {Calcium carbonate; Pigment white 18; Lithographic stone}	10.0 -30.0 %	EV9580000
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	5.0 -10.0 %	WJ8925000
26813-14-9	Synthetic polyterpene resin	5.0 -10.0 %	NA
106-97-8	Butane	5.0 -10.0 %	EJ4200000
74-98-6	Propane {Dimethyl methane; Propyl hydride}	5.0 -10.0 %	TX2275000
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	5.0 -10.0 %	DC3325000
7631-86-9	Silica {Diatomaceous earth; Silicon dioxide; Pigment white 27}	1.0 -5.0 %	EU8655000
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	1.0 -5.0 %	ZE2100000

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

## 4. FIRST AID MEASURES

### Emergency and First Aid Procedures:

#### Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

#### Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

#### Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

#### Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

### Signs and Symptoms Of Exposure:

See Potential Health Effects

### Note to Physician:

Inhalation overexposure can produce toxic effects. Monitor for respiratory distress. If cough or difficulty in breathing develops, evaluate for upper respiratory tract inflammation, bronchitis, and pneumonitis. Administer supplemental oxygen with assisted ventilation, as required.

Toluene sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. Administration of sympathomimetic drugs should be avoided.

Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

## 5. FIRE FIGHTING MEASURES

**Flash Pt:** Level 3 Aerosol

**Explosive Limits:** No data.

LEL: No data. UEL: No data.

**Autoignition Pt:** No data.

**Suitable Extinguishing Media:** Use carbon dioxide, dry powder, water spray, or foam.

**Unsuitable Extinguishing Media:** None known.

**Fire Fighting Instructions:** Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from containers that have been exposed to intense heat or flame.

Flammable aerosols. Containers may explode when heated.

**Flammable Properties and Hazards:** Flashpoint of liquid concentrate: 70 Fahrenheit (Setaflash Closed Cup)

Flashpoint of propellant: -132.23 Fahrenheit (closed cup)

**Flammability Classification:**

## 6. ACCIDENTAL RELEASE MEASURES

**Steps To Be Taken In Case Material Is Released Or Spilled:** Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Spills: Take up with sand, earth or other noncombustible absorbent material and place in a closed container.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions To Be Taken in Handling:** Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

**Precautions To Be Taken in Storing:** Store in a cool, dry place. Do not store near flames or at elevated temperatures. Keep out of direct sunlight.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
108-88-3	Toluene {Benzene, Methyl-; Toluol}	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 50 ppm	No data.
64742-95-6	Petroleum Hydrocarbons	No data.	No data.	No data.
1317-65-3	Limestone {Calcium carbonate; Pigment white 18; Lithographic stone}	PEL: 15 (dust); 5 (resp.) mg/m3	No data.	No data.
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	PEL: 500 ppm	TLV: 200 mg/m3	No data.
26813-14-9	Synthetic polyterpene resin	No data.	No data.	No data.
106-97-8	Butane	No data.	TLV: (800 ppm)	No data.
74-98-6	Propane {Dimethyl methane; Propyl hydride}	PEL: 1000 ppm	TLV: (2500 ppm)	No data.

# SAFETY DATA SHEET

## Home Armor Flexible Sealer

Page: 6

Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 01/29/2014

95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	No data.	No data.	No data.
7631-86-9	Silica {Diatomaceous earth; Silicon dioxide; Pigment white 27}	No data.	No data.	No data.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.

**Respiratory Equipment (Specify Type):** For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

**Eye Protection:** Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.

**Protective Gloves:** Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

**Other Protective Clothing:** Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

**Engineering Controls (Ventilation etc.):** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

**Work/Hygienic/Maintenance Practices:** Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical States:</b>	[ X ] Gas	[ X ] Liquid	[ ] Solid
<b>Appearance and Odor:</b>	Thick black liquid.		
<b>Melting Point:</b>	No data.		
<b>Boiling Point:</b>	No data.		
<b>Autoignition Pt:</b>	No data.		
<b>Flash Pt:</b>	No data.		
<b>Explosive Limits:</b>	LEL: No data.	UEL: No data.	
<b>Specific Gravity (Water = 1):</b>	0.929 - gm/liter		
<b>Density:</b>	8.1 - 8.4 LB/GL		
<b>Vapor Pressure (vs. Air or mm Hg):</b>	No data.		
<b>Vapor Density (vs. Air = 1):</b>	> 1		
<b>Evaporation Rate:</b>	> 1 (BuAC=1)		
<b>Solubility in Water:</b>	None		
<b>Percent Volatile:</b>	68.37 % by weight.		
<b>VOC / Volume:</b>	617.0000 G/L		
<b>Additional Physical Information</b>	VOC (G/L) is for concentrate		

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Unstable [ ]	Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	No data available.	
<b>Incompatibility - Materials To Avoid:</b>	Strong acids, strong bases, alkalies, and oxidizers such as liquid chlorine, other halogens, hydrogen peroxide and oxygen.	
<b>Hazardous Decomposition Or Byproducts:</b>	Carbon monoxide, carbon dioxide, unburned hydrocarbons, aldehydes and other products of incomplete combustion, nitrogen oxides, sulfur oxides	
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ]	Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	No data available.	

## 11. TOXICOLOGICAL INFORMATION

<b>Toxicological Information:</b>	This product has not been tested as a whole. Refer to section 2 for acute and chronic health effects.
<b>Chronic Toxicological Effects:</b>	<p>CAS# 108-88-3: Reproductive Effects:, TClO, Inhalation, Rat, 800.0 MG/M3, 6 H, female 14-20 day(s) after conception. Result: Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Effects on Newborn: Behavioral. - Brazilian Journal of Medical and Biological Research., Vol/p/yr: 23,533, 1990</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 2.000 MG, 24 H, Severe. Result: Effects on Embryo or Fetus: Other effects to embryo. Specific Developmental Abnormalities: Eye, ear. - Prehled Prumyslove Toxikologie, Marhold, J., Organicke Latky, Prague Czechoslovakia, Vol/p/yr: -,29, 1986</p> <p>CAS# 64742-95-6: Acute toxicity, LD50, Oral, Rat, 8400. MG/KG. Result: Behavioral: Somnolence (general depressed activity). Behavioral: Tremor. Lungs, Thorax, or Respiration:Other changes. - National Technical Information Service, Vol/p/yr: OTS0534799,</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 100.0 UL, 24 H, Mild. Result: Brain and Coverings: Changes in surface EEG. Blood:Changes in serum composition (e.g. Related to Chronic Data - changes in testicular weight. - National Technical Information Service, Vol/p/yr: OTS0534779,</p> <p>CAS# 1330-20-7: Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H. Result: Behavioral: Muscle contraction or spasticity. Lungs, Thorax, or Respiration:Other changes. - Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe. Result: Behavioral: General anesthetic. Behavioral: Somnolence (general depressed activity). Behavioral: Irritability. - "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972</p>



# SAFETY DATA SHEET

## Home Armor Flexible Sealer

Page: 9

Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 01/29/2014

This product has not been tested as a whole.

**Carcinogenicity/Other Information:**

IARC 3: Not Classifiable as to Carcinogenicity in Humans.

ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
108-88-3	Toluene {Benzene, Methyl-; Toluol}	n.a.	3	A4	n.a.
64742-95-6	Petroleum Hydrocarbons	n.a.	n.a.	n.a.	n.a.
1317-65-3	Limestone {Calcium carbonate; Pigment white 18; Lithographic stone}	n.a.	n.a.	n.a.	n.a.
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	n.a.	n.a.	n.a.	n.a.
26813-14-9	Synthetic polyterpene resin	n.a.	n.a.	n.a.	n.a.
106-97-8	Butane	n.a.	n.a.	n.a.	n.a.
74-98-6	Propane {Dimethyl methane; Propyl hydride}	n.a.	n.a.	n.a.	n.a.
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	n.a.	n.a.	n.a.	n.a.
7631-86-9	Silica {Diatomaceous earth; Silicon dioxide; Pigment white 27}	Known	3	n.a.	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.

## 12. ECOLOGICAL INFORMATION

**General Ecological Information:**

This product has not been tested as a whole.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:**

Dispose of in accordance with local, state, and federal laws.

Do not place material in general trash.

Do not allow material to enter bodies of water or sewers.

## 14. TRANSPORT INFORMATION

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Aerosols, flammable, Ltd. Qty.  
**DOT Hazard Class:** 2.1 FLAMMABLE GAS  
**UN/NA Number:** UN1950  
**Precautionary Label:** Level 3 Aerosol

**Additional Transport Information:**

The shipper/supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

# SAFETY DATA SHEET

## Home Armor Flexible Sealer

### 15. REGULATORY INFORMATION

#### EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
108-88-3	Toluene {Benzene, Methyl-; Toluol}	No	Yes 1000 LB	Yes
64742-95-6	Petroleum Hydrocarbons	No	No	No
1317-65-3	Limestone {Calcium carbonate; Pigment white 18; Lithographic stone}	No	No	No
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	No	No	No
26813-14-9	Synthetic polyterpene resin	No	No	No
106-97-8	Butane	No	No	No
74-98-6	Propane {Dimethyl methane; Propyl hydride}	No	No	No
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	No	No	Yes
7631-86-9	Silica {Diatomaceous earth; Silicon dioxide; Pigment white 27}	No	No	No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes 100 LB	Yes

**This material meets the EPA**  Yes  No Acute (immediate) Health Hazard  
**'Hazard Categories' defined**  Yes  No Chronic (delayed) Health Hazard  
**for SARA Title III Sections**  Yes  No Fire Hazard  
**311/312 as indicated:**  Yes  No Sudden Release of Pressure Hazard  
 Yes  No Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
108-88-3	Toluene {Benzene, Methyl-; Toluol}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes
64742-95-6	Petroleum Hydrocarbons	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
1317-65-3	Limestone {Calcium carbonate; Pigment white 18; Lithographic stone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
26813-14-9	Synthetic polyterpene resin	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
106-97-8	Butane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
74-98-6	Propane {Dimethyl methane; Propyl hydride}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
7631-86-9	Silica {Diatomaceous earth; Silicon dioxide; Pigment white 27}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No

## 16. OTHER INFORMATION

**Revision Date:** 05/04/2015

**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About** No data available.

**This Product:**

**Company Policy or**

**Disclaimer:**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.